



KÖSTER Butyl Fix-Tape Fleece

Cold self adhesive, fleece laminated butyl waterproofing tape for KÖSTER KSK membrane to plaster transitions, 1.5 mm x 150 mm

Features

KÖSTER Butyl Fix-Tape Fleece is a butyl / rubber, fleece laminated waterproofing tape. It is cold self adhesive, 1.5 mm thick, with a protective foil on the adhesive side. The material can be applied directly from the roll. It is highly tear resistant, immediately waterproof, and it can be covered with plaster due to its fleece laminated upper side. Priming before application of the KÖSTER Butyl Fix-Tape Fleece is not necessary.

KÖSTER KSK ALU Strong
KÖSTER KSK Primer BL
KÖSTER KBE Liquid Film
KÖSTER Fix-Tape 10 ALU
KÖSTER Fix-Tape 15 DS
KÖSTER KSK ALU 15
KÖSTER KSK SY 15
KÖSTER Universal Cleaner

Prod. code R 817 105 AS
Prod. code W 120 015
Prod. code W 245
Prod. code W 810 AL
Prod. code W 815 020 DS
Prod. code W 815 096 AL
Prod. code W 815 105
Prod. code X 910 010

Technical Data

Material	Butyl / Rubber
Width	15 cm
Thickness	1.5 mm
Temperature resistance	- 25 °C to + 80 °C
Application temperature	+ 5 °C to + 30 °C
μ-value	approx. 135,000
Sd-value	approx. 203 m

Fields of Application

KÖSTER Butyl Fix-Tape Fleece is designed for securing upper connections of KÖSTER KSK membranes on solid, clean, dry, dust and oil free substrates.

Substrate

When installing KÖSTER KSK waterproofing membranes, the chosen primer must be raised above the membrane so that the KÖSTER Butyl Fix-Tape Fleece is flush on the top side.

When using the KÖSTER Butyl Fix-Tape Fleece alone, KÖSTER KBE Liquid Film and KÖSTER KSK Primer BL are suitable as a primer.

Application

After waterproofing with KÖSTER KSK membranes, KÖSTER Butyl Fix-Tape Fleece is attached on the upper end of the waterproofing membranes, evenly covering the transition between KÖSTER KSK membranes and the substrate. In this manner a transition can be made between plaster and waterproofing. Prior to application, the protective backing paper on the adhesive side of the tape must be removed.

Firmly press the applied tapes onto the substrate using a KÖSTER Rubber Hand Roller. The laminated fleece on the upper side of the tape allows it can be covered with plaster on foundation splash zones.

Cleaning

Clean cutting tools with KÖSTER Universal Cleaner.

Packaging

W 815 015 F 10 m roll

Storage

Store the material dry at temperatures between + 5 °C and + 30 °C. It can be stored for a minimum of 1 year.

Related products

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The proper and thereby effective and successful application of our products is not subject to our control. The installer is responsible for the correct application under consideration of the specific conditions of the construction site and for the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which exceed the specifications contained in this technical guideline require written confirmation. The valid standards for testing and installation, technical guidelines, and acknowledged rules of technology have to be adhered to at all times. The warranty can and is therefore only applied to the quality of our products within the scope of our terms and conditions, not however, for their effective and successful application. This guideline has been technically revised; all previous versions are invalid.